## **Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims:**

1. (Currently amended) A method for providing a predetermined transmission rate for an auxiliary information in a predetermined channel of a data transmission stream, said method comprising the steps of:

setting for said data transmission stream an additional combination of selectable transport formats, which determines a maximum allowable data rate higher by a predetermined rate amount than the maximum data rate of a signal transmitted via said predetermined channel, into a predetermined set of selectable combinations of selectable transport formats; and

using said predetermined rate amount of said predetermined channel to transmit said auxiliary information.

- 2. (Original) A method according to claim 1, wherein said transmission stream is a multiplex signal having at least one channel, and said selectable transport formats can be allocated to said at least one channel.
- 3. (Currently amended) A method according to claim 2, wherein said setting step comprises adding to a set of transport format combinations selectable for said at least one channel a new transport format combination which determines for said predetermined channel a new transport format leading to said maximum allowable data rate.
- 4. (Original) A method according to claim 3, wherein said new transport format combination comprises a transport format selected for said predetermined channel from a set of existing transport formats allocated to said predetermined channel, said selected transport format leading to an additional maximum allowable data rate for said transmission stream.
- 5. (Currently amended) A method according to claim 2, wherein said setting step comprises adding to said data transmission stream a new channel, and allocating to said new

channel a set of selectable transport formats comprising a transport format which determines said maximum allowable data rate.

- 6. (Currently amended) A method according to claim 2, wherein said setting step comprises setting a restriction for using only a subset of selectable transport format combinations for said data transmission stream.
- 7. (Currently amended) A method according to claim <u>12</u>, wherein said predetermined channel is located at a predetermined fixed position within said at least one channel.
- 8. (Original) A method according to claim 7, wherein said fixed position corresponds to the last channel position within a frame of said data transmission stream.
- 9. (Original) A method according to claim 1, wherein said maximum allowable data rate defines transport blocks of a predetermined size in said data transmission stream.
- 10. (Original) A method according to claim 1, wherein said auxiliary information comprises a discontinuous transmission information.
- 11. (Original) A method according to claim 1, wherein said channel is a dedicated channel.
- 12. (Original) A method according to claim 1, wherein said data transmission stream is a downlink signal of a cellular network.
- 13. (Original) A method according to claim 1, wherein said auxiliary information is replaced by a control information.
- 14. (Original) A method according to claim 13, wherein said control information comprises HSDPA signaling information.
- 15. (Currently amended) A device for providing a predetermined transmission rate for an auxiliary information in a predetermined channel of a data transmission stream, said system comprising:

setting means for setting for said data transmission stream an additional combination of selectable transport formats, which determines a maximum allowable data rate higher by a predetermined rate amount than the maximum data rate of a signal transmitted via said <u>predetermined</u> channel, into a predetermined set of selectable combinations of selectable transport formats; and

transmission means for transmitting said auxiliary information in said channel by using said predetermined rate amount.

- 16. (Currently amended) A device according to claim 15, wherein said setting means is arranged to add to a set of transport format combinations selectable for said at least one channel a new transport format combination which determines for said predetermined channel a new transport format leading to said maximum allowable data rate.
- 17. (Original) A device according to claim 16, wherein said new transport format combination comprises a frame format selected for said predetermined channel from a set of existing frame formats allocated to said predetermined channel, said selected frame format defining for said predetermined channel said maximum allowable data rate.
- 18. (Original) A device according to claim 15, wherein said setting means is arranged to add to said data transmission stream a new channel, and to allocate to said new channel a set of selectable transport formats comprising a transport format which determines said maximum allowable data rate.
- 19. (Original) A device according to claim 15, wherein said setting means is arranged to set a restriction for using only a subset of selectable transport format combinations for said signal transmitted via said predetermined channel.
- 20. (Original) A device according to claim 15, wherein said device is a base station device.